AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

- 1-8. (Canceled)
- 9. (Currently amended) A 2D/3D switching type liquid crystal display panel, comprising: display image generating means, capable of carrying out 2D display and 3D display, for generating a display image according to input image data;

parallax barrier means for giving a specific viewing angle to the display image in carrying out 3D display, so as to obtain a 3D effect; and

switching means for activating and inactivating the effect of the parallax barrier means, so as to switch 2D display and 3D display,

said display image generating means being a transflective liquid crystal display panel including:

- a reflective region for performing reflective display; and
- a transmissive region for performing transmissive display,

the reflective region and the transmissive region being provided for each pixel, and a diffuser processed layer provided being-performed only in a portion corresponding to the reflective region.

10. (Currently amended) A 2D/3D switching type liquid crystal display, comprising a 2D/3D switching type liquid crystal display panel including:

display image generating means, capable of carrying out 2D display and 3D display, for generating a display image according to input image data;

parallax barrier means for giving a specific viewing angle to the display image in carrying out 3D display, so as to obtain a 3D effect; and

switching means for activating and inactivating the effect of the parallax barrier means, so as to switch 2D

display and 3D display,

said display image generating means being a transflective liquid crystal display panel including:

a reflective region for performing reflective display; and

a transmissive region for performing transmissive display,

the reflective region and the transmissive region being provided for each pixel, and a diffuser processed layer provided substantially being performed only in a portion corresponding to the reflective region.

11. (Currently amended) A liquid crystal display panel, comprising:

display image generating means for generating two display images according to input image data;

parallax barrier means for separating the two display images into different viewing angles; and

switching means for activating and inactivating the effect of the parallax barrier means, said display image generating means being a transflective liquid crystal display panel including:

a reflective region for performing reflective display; and

a transmissive region for performing transmissive

TANAKA et al Appl. No. 10/529,225 June 28, 2007

display,

the reflective region and the transmissive region being provided for each pixel, and a diffuser processed layer provided substantially being performed only in a portion corresponding to the reflective region.

12. (Currently amended) A liquid crystal display, comprising a liquid crystal display panel including:

display image generating means for generating two display images according to input image data;

parallax barrier means for separating the two display images into different viewing angles; and

switching means for activating and inactivating the effect of the parallax barrier means, said display image generating means being a transflective liquid crystal display panel including:

a reflective region for performing reflective display; and

a transmissive region for performing transmissive display,

the reflective region and the transmissive region being provided for each pixel, and a diffuser processed layer provided substantially being performed only in a portion corresponding to the reflective region.

13. (New) The panel of claim 9, wherein the diffuser processed layer is subjected to a diffuser process which makes resin light scattering by inclusion of particles in a resin of the

TANAKA et al Appl. No. 10/529,225 June 28, 2007

diffuser processed layer, the particles having a different refractive index from a refractive index of the resin.

14. (New) The panel of claim 10, wherein the diffuser processed layer is subjected to a diffuser process which makes resin light scattering by inclusion of particles in a resin of the diffuser processed layer, the particles having a different refractive index from a refractive index of the resin.

15. (New) The panel of claim 11, wherein the diffuser processed layer is subjected to a diffuser process which makes resin light scattering by inclusion of particles in a resin of the diffuser processed layer, the particles having a different refractive index from a refractive index of the resin.

16. (New) The panel of claim 12, wherein the diffuser processed layer is subjected to a diffuser process which makes resin light scattering by inclusion of particles in a resin of the diffuser processed layer, the particles having a different refractive index from a refractive index of the resin.

17. (New) The panel of claim 9, wherein a transparent layer, disposed opposite a reflective electrode with a liquid crystal layer in between, is subjected to a diffuser process so a to form the diffuser processed layer.

TANAKA et al Appl. No. 10/529,225 June 28, 2007

18. (New) The panel of claim 10, wherein a transparent layer, disposed opposite a reflective electrode with a liquid crystal layer in between, is subjected to a diffuser process so a to form the diffuser processed layer.

19. (New) The panel of claim 11, wherein a transparent layer, disposed opposite a reflective electrode with a liquid crystal layer in between, is subjected to a diffuser process so a to form the diffuser processed layer.

20. (New) The panel of claim 12, wherein a transparent layer, disposed opposite a reflective electrode with a liquid crystal layer in between, is subjected to a diffuser process so a to form the diffuser processed layer.